

NEW



Art.	Description
------	-------------

MOTOR DEADBOLT FOR AUTOMATIC GATES LEGION SERIES

Version: for surface fixing

Lock body in stainless steel, aluminium cover with plastic ends
Dimensions: 515 x 42 x 58

Mechanical opening with Euro-profile cylinder (from both sides)
Cylinder not included - stainless steel fixing plate included
To select the length of the cylinder see page 167

Steel made bolt diameter (mm) 18 x extension 55 (stroke 55)
Bolt "total reaction" burglar device in closed position

C. / N.O. / N.C. output contact
Operating voltage: 10 - 30Vdc
Absorbed current 300Ma at 12vDC

**Internal self-heating – when temperature drops under 5°C , coil
warms-up to avoid freezing.**


Time adjustment between 0-5 seconds from re-locking after door opening
and between 0-60 seconds if door is not opened

Fail locked version - Deadbolt closed without power

28720
28720N

Carter in satin anodised finish
Carter in black anodised finish

Use: high security solenoid lock for automatic gates. It can be used
downward, upward and horizontally.



With internal self-heating

02290

FLOOR STRIKE

Stainless steel striking plate for bolt insertion into the floor.
For item 28700 – 28710 - 28720 – 28800 – 28800LC
Dimension : mm 120 diameter x 5mm thickness

